

View Online at <https://aerobasegroup.com/nsn/5340-00-987-9095>

Fabrication Method (non-core):

Stamped

First Leg Length:

1.094 inches

Second Leg Length:

1.375 inches

Second Leg Width:

3.125 inches

Second Leg End Width:

2.375 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Hole Diameter:

0.266 inches

Second Leg Distance Between Hole Centers Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.562 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

3.125 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.000 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.562 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl2 federal specification all treatment responses

Style Designator:

Angle

Fsc Application Data:

Radar transmitting sets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0