

View Online at <https://aerobasegroup.com/nsn/5340-00-988-4861>

Fabrication Method (non-core):

Machined

Second Leg Length:

Between 0.725 inches and 0.745 inches

Second Leg Width:

1.618 inches

Second Leg Corner Radius:

0.250 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Distance Between Hole Centers Along Width:

1.118 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.220 inches

First Leg Thickness:

Between 0.056 inches and 0.062 inches

Second Leg Thickness:

Between 0.056 inches and 0.062 inches

Center Section Height:

1.604 inches

Center Section Thickness:

Between 0.056 inches and 0.062 inches

First Leg Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.230 inches

First Leg End Radius:

0.375 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

First Leg Offset Angle:

30.0 degrees

Material:

Titanium alloy

Material Specification:

Ams4910 assn standard single material response

Style Designator:

Offset double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0