

View Online at <https://aerobasegroup.com/nsn/5340-00-989-2983>

Thread Class:

3a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

2.130 inches rod connection and 2.250 inches rod connection

Shank Length:

Between 2.370 inches and 2.390 inches

Hole Diameter:

Between 0.3119 inches and 0.3122 inches

Shank Diameter:

0.562 inches

Overall Height:

Between 0.615 inches and 0.635 inches

Overall Width:

Between 1.256 inches and 1.298 inches

End Radius:

Between 0.365 inches and 0.385 inches

Fork Span Width:

Between 0.876 inches and 0.878 inches

Rod Connection Bore Diameter:

Between 0.240 inches and 0.260 inches

Rod Connection Bore Depth:

Between 1.910 inches and 1.970 inches

Distance From Pivot Pinhole Center To Rod Connection End:

Between 3.850 inches and 3.910 inches

Fork Arm Thickness:

0.190 mils and 0.210 centimeters

Fork Depth:

Between 0.970 inches and 1.030 inches

Thread Size:

0.562 inches rod connection

Material:

Steel comp 4130

Material Specification:

Mil-s-6758, cond d4 or f4 military specification single material response

Surface Treatment:

Chromate zinc and cadmium

Surface Treatment Specification:

299-099-031, pzg1, bell helicopter co mfr ref single treatment response and 299-099-031, cb1, bell helicopter co mfr ref single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A264a0

Mil-std (military Standard):

Mil-s-6758 spec.