

View Online at <https://aerobasegroup.com/nsn/5340-00-989-2983>

**Thread Class:**

3a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

2.130 inches rod connection and 2.250 inches rod connection

**Shank Length:**

Between 2.370 inches and 2.390 inches

**Hole Diameter:**

Between 0.3119 inches and 0.3122 inches

**Shank Diameter:**

0.562 inches

**Overall Height:**

Between 0.615 inches and 0.635 inches

**Overall Width:**

Between 1.256 inches and 1.298 inches

**End Radius:**

Between 0.365 inches and 0.385 inches

**Fork Span Width:**

Between 0.876 inches and 0.878 inches

**Rod Connection Bore Diameter:**

Between 0.240 inches and 0.260 inches

**Rod Connection Bore Depth:**

Between 1.910 inches and 1.970 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 3.850 inches and 3.910 inches

**Fork Arm Thickness:**

0.190 mils and 0.210 centimeters

**Fork Depth:**

Between 0.970 inches and 1.030 inches

**Thread Size:**

0.562 inches rod connection

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758, cond d4 or f4 military specification single material response

**Surface Treatment:**

Chromate zinc and cadmium

**Surface Treatment Specification:**

299-099-031, pzg1, bell helicopter co mfr ref single treatment response and 299-099-031, cb1, bell helicopter co mfr ref single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A264a0

**Mil-std (military Standard):**

Mil-s-6758 spec.