

View Online at <https://aerobasegroup.com/nsn/5340-00-995-2731>

First Leg Length:

1.560 inches

Second Leg Length:

1.560 inches

Reinforcement Method (non-core):

Beaded center section

Second Leg Width:

0.620 inches

Second Leg End Width:

0.260 inches

First Leg Hole Diameter:

0.098 inches

Second Leg Hole Diameter:

0.098 inches

Second Leg Distance Between Hole Centers Along Length:

0.620 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

0.620 inches

First Leg End Width:

0.260 inches

First Leg Distance Between Hole Centers Along Length:

0.620 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Surface Treatment:

Anodize and chromate

Surface Treatment Specification:

Mil-c-5541 military specification 1st treatment response or mil-a-8625 military specification 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.