

View Online at <https://aerobasegroup.com/nsn/5340-00-998-2768>

First Leg Length:

1.510 inches

Second Leg Length:

1.640 inches

Second Leg Width:

Between 0.590 inches and 0.650 inches

First Leg Hole Diameter:

Between 0.097 inches and 0.100 inches

Second Leg Hole Diameter:

Between 0.097 inches and 0.100 inches

Second Leg Distance Between Hole Centers Along Length:

0.720 mils and 0.780 centimeters

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.340 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.340 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

Between 0.590 inches and 0.650 inches

First Leg Distance Between Hole Centers Along Length:

Between 0.590 inches and 0.650 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.340 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.340 inches

First Leg End Radius:

Between 0.400 inches and 0.460 inches

Second Leg End Radius:

Between 0.400 inches and 0.460 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Offset Angle:

6.0 degrees

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-250/13, t6 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Offset angle

Specification Data:

78286-s1082 manufacturers specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.