NSN 5340-00-998-5286

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-998-5286

Fabrication Method (non-core):
Machined
First Leg Length:
0.520 inches
Second Leg Length:
0.770 inches
Second Leg Width:
0.620 inches
First Leg Hole Diameter:
0.281 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.310 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.350 inches
Second Leg Slot Length:
0.460 inches
Second Leg Slot Width:
0.230 inches
First Leg Thickness:
0.052 inches
Second Leg Thickness:
0.052 inches
Center Section Height:
0.430 inches
Center Section Width:
0.620 inches
Center Section Thickness:
0.052 inches
First Leg Width:
0.620 inches
First Leg Distance From Edge To Hole Center Along Width:
0.310 inches
First Leg Distance From Edge To Hole Center Along Length:
0.220 inches
First Leg End Radius:
0.450 inches
Second Leg End Radius:
0.450 inches
First Leg Style:
End radius
First Leg Hole Arrangement Style:

One hole

NSN 5340-00-998-5286

Double Angle Bracket - Page 2 of 2



Second Leg Style:	
End radius	
Second Leg Hole Arrangement Style:	
One hole	
First Leg Angle:	
135.0 degrees	
Second Leg Angle:	
135.0 degrees	
Material:	
Steel comp 321	
Material Specification:	
Fed standard 66, aisi 321/sae 30321 assn standard single material response	
Style Designator:	
Double angle	
Fsc Application Data:	
Engine, acft, turbo jet	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A042a0	