

View Online at <https://aerobasegroup.com/nsn/5340-00-998-5286>

Fabrication Method (non-core):

Machined

First Leg Length:

0.520 inches

Second Leg Length:

0.770 inches

Second Leg Width:

0.620 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.350 inches

Second Leg Slot Length:

0.460 inches

Second Leg Slot Width:

0.230 inches

First Leg Thickness:

0.052 inches

Second Leg Thickness:

0.052 inches

Center Section Height:

0.430 inches

Center Section Width:

0.620 inches

Center Section Thickness:

0.052 inches

First Leg Width:

0.620 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.220 inches

First Leg End Radius:

0.450 inches

Second Leg End Radius:

0.450 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

First Leg Angle:

135.0 degrees

Second Leg Angle:

135.0 degrees

Material:

Steel comp 321

Material Specification:

Fed standard 66, aisi 321/sae 30321 assn standard single material response

Style Designator:

Double angle

Fsc Application Data:

Engine, acft, turbo jet

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0