

View Online at <https://aerobasegroup.com/nsn/5340-00-999-6441>

Fabrication Method (non-core):

Stamped

First Leg Length:

3.000 inches

Second Leg Length:

4.000 inches

Second Leg Width:

17.000 inches

First Leg Hole Diameter:

Between 0.529 inches and 0.539 inches

Second Leg Hole Diameter:

Between 0.530 inches and 0.540 inches

Second Leg Distance Between Hole Centers Along Width:

4.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

9.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

17.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

3.000 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

3.000 inches

First Leg Distance From Edge To Hole Center Along Width:

10.030 inches

First Leg Distance From Edge To Hole Center Along Length:

1.250 inches

First Leg Style:

Angle

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Chamfer opposite second leg end width, one hole in second leg 0.779 in. Min, 0.789 in. Dia. Max

Material:

Steel comp 1010 or steel comp 1020

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0