

View Online at <https://aerobasegroup.com/nsn/5340-01-006-3999>

First Leg Length:

Between 1.120 inches and 1.160 inches

Second Leg Length:

Between 1.490 inches and 1.550 inches

Second Leg Width:

Between 1.242 inches and 1.246 inches

Second Leg Corner Radius:

Between 0.240 inches and 0.260 inches

First Leg Slot Length:

Between 0.420 inches and 0.460 inches

First Leg Slot Width:

Between 0.210 inches and 0.230 inches

Second Leg Hole Diameter:

Between 0.337 inches and 0.351 inches

Second Leg Distance Between Hole Centers Along Width:

1.194 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

1.194 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.360 inches and 0.390 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.380 inches and 0.460 inches

First Leg End Radius:

Between 0.360 inches and 0.390 inches

First Leg Style:

End radius and tapered

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Mounting hole type: plain and slotted

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0