

View Online at <https://aerobasegroup.com/nsn/5340-01-006-4000>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.938 inches

Second Leg Length:

2.500 inches

Second Leg Width:

0.750 inches

Second Leg Corner Radius:

0.188 inches

First Leg Hole Diameter:

Between 0.098 inches and 0.101 inches

Second Leg Hole Diameter:

Between 0.219 inches and 0.233 inches

Second Leg Distance Between Hole Centers Along Length:

0.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.375 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.072 inches

Second Leg Thickness:

0.072 inches

First Leg Width:

0.750 inches

First Leg Corner Radius:

0.188 inches

First Leg Distance Between Hole Centers Along Width:

0.375 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.188 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

0.188 inches

First Leg Distance From Edge To Hole Center Along Width:

0.188 inches

First Leg Distance From Edge To Hole Center Along Length:

0.188 inches

First Leg Distance Between First And Second Hole Centers Along Length:

0.188 inches

First Leg Distance Between Second And Third Hole Centers Along Length:

0.188 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, alclad t3 federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0