

View Online at <https://aerobasegroup.com/nsn/5340-01-007-1685>

**First Leg Length:**

0.750 inches

**Second Leg Length:**

0.800 inches

**First Leg Hole Diameter:**

0.129 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.300 inches

**Second Leg Slot Length:**

Between 0.494 inches and 0.514 inches

**Second Leg Slot Width:**

Between 0.224 inches and 0.234 inches

**First Leg Thickness:**

0.071 inches

**Second Leg Thickness:**

0.071 inches

**First Leg Width:**

1.000 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Furnished with cres clip nut; mounting hole type: plain and slotted

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Angle

**Specification Data:**

76301-st9-496 manufacturers specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.