NSN 5340-01-007-8250

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-007-8250

First Leg Length:

Between 0.615 inches and 0.635 inches

Second Leg Length:

Between 0.990 inches and 1.010 inches

Second Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Hole Diameter:

Between 0.249 inches and 0.255 inches

Second Leg Hole Diameter:

Between 0.194 inches and 0.204 inches

Second Leg Distance Between Hole Centers Along Length:

0.365 mils and 0.385 centimeters

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.270 inches

First Leg Thickness:

Between 0.053 inches and 0.073 inches

Second Leg Thickness:

Between 0.053 inches and 0.073 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.270 inches

First Leg End Radius:

Between 0.230 inches and 0.270 inches

Second Leg End Radius:

Between 0.230 inches and 0.270 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

NSN 5340-01-007-8250

Angle Bracket - Page 2 of 2

Fiig: A042a0



| Material: |
|--|
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-250/5, alclad t3 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |