

View Online at <https://aerobasegroup.com/nsn/5340-01-008-6911>

First Leg Length:

Between 0.820 inches and 0.860 inches

Second Leg Length:

2.326 inches

Second Leg Width:

0.899 inches

First Leg Slot Length:

Between 0.400 inches and 0.440 inches

First Leg Slot Width:

Between 0.200 inches and 0.220 inches

Second Leg Distance Between Hole Centers Along Length:

1.556 mils and 1.566 centimeters

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.545 inches and 0.555 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.360 inches and 0.380 inches

Second Leg Slot Length:

Between 0.400 inches and 0.440 inches

Second Leg Slot Width:

Between 0.200 inches and 0.220 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

0.680 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.495 inches and 0.505 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.360 inches and 0.380 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0