

View Online at <https://aerobasegroup.com/nsn/5340-01-009-4511>

Fabrication Method (non-core):

Machined

Mounting Hole Type:

Threaded and countersunk

First Leg Length:

Between 0.520 inches and 0.540 inches

Second Leg Length:

Between 1.220 inches and 1.250 inches

Second Leg Width:

Between 0.800 inches and 0.820 inches

First Leg Hole Diameter:

0.250 inches

Second Leg Hole Diameter:

Between 0.499 inches and 0.506 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.400 inches and 0.410 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.520 inches and 0.550 inches

First Leg Thickness:

Between 0.190 inches and 0.200 inches

Second Leg Thickness:

Between 0.150 inches and 0.160 inches

First Leg Width:

Between 0.800 inches and 0.820 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.400 inches and 0.410 inches

First Leg Distance From Edge To Hole Center Along Length:

0.300 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 302 or steel comp 304

Material Specification:

Qq-s-766, cond a federal specification all material responses

Surface Treatment:

Passivate

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0