

View Online at <https://aerobasegroup.com/nsn/5340-01-009-4511>

**Fabrication Method (non-core):**

Machined

**Mounting Hole Type:**

Threaded and countersunk

**First Leg Length:**

Between 0.520 inches and 0.540 inches

**Second Leg Length:**

Between 1.220 inches and 1.250 inches

**Second Leg Width:**

Between 0.800 inches and 0.820 inches

**First Leg Hole Diameter:**

0.250 inches

**Second Leg Hole Diameter:**

Between 0.499 inches and 0.506 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.400 inches and 0.410 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.520 inches and 0.550 inches

**First Leg Thickness:**

Between 0.190 inches and 0.200 inches

**Second Leg Thickness:**

Between 0.150 inches and 0.160 inches

**First Leg Width:**

Between 0.800 inches and 0.820 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.400 inches and 0.410 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.300 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 302 or steel comp 304

**Material Specification:**

Qq-s-766, cond a federal specification all material responses

**Surface Treatment:**

Passivate

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0