

View Online at <https://aerobasegroup.com/nsn/5340-01-010-5384>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

Between 0.697 inches and 0.749 inches

**Second Leg Length:**

Between 1.287 inches and 1.339 inches

**Second Leg Width:**

Between 0.480 inches and 0.520 inches

**First Leg Slot Length:**

Between 0.390 inches and 0.420 inches

**First Leg Slot Width:**

Between 0.200 inches and 0.210 inches

**Second Leg Hole Diameter:**

Between 0.204 inches and 0.214 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.170 inches and 0.190 inches

**First Leg Thickness:**

Between 0.057 inches and 0.069 inches

**Second Leg Thickness:**

Between 0.057 inches and 0.069 inches

**First Leg Width:**

Between 0.480 inches and 0.520 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.265 inches and 0.295 inches

**First Leg End Radius:**

Between 0.460 inches and 0.500 inches

**Second Leg End Radius:**

Between 0.460 inches and 0.500 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 321

**Material Specification:**

Ams 5510 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0