

View Online at <https://aerobasegroup.com/nsn/5340-01-010-5384>

Fabrication Method (non-core):

Stamped

First Leg Length:

Between 0.697 inches and 0.749 inches

Second Leg Length:

Between 1.287 inches and 1.339 inches

Second Leg Width:

Between 0.480 inches and 0.520 inches

First Leg Slot Length:

Between 0.390 inches and 0.420 inches

First Leg Slot Width:

Between 0.200 inches and 0.210 inches

Second Leg Hole Diameter:

Between 0.204 inches and 0.214 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.170 inches and 0.190 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 0.480 inches and 0.520 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.265 inches and 0.295 inches

First Leg End Radius:

Between 0.460 inches and 0.500 inches

Second Leg End Radius:

Between 0.460 inches and 0.500 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0