

View Online at <https://aerobasegroup.com/nsn/5340-01-019-7070>

**Thread Class:**

3b rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

0.906 inches rod connection

**Hole Diameter:**

Between 0.124 inches and 0.129 inches

**Overall Height:**

Between 0.420 inches and 0.440 inches

**Overall Width:**

Between 0.360 inches and 0.380 inches

**Fork Span Width:**

Between 0.155 inches and 0.165 inches

**Securing Pin Hole Diameter:**

Between 0.057 inches and 0.067 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

Between 0.240 inches and 0.260 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 1.479 inches and 1.489 inches

**Fork Arm Thickness:**

0.098 mils and 0.113 centimeters

**Fork Depth:**

Between 1.079 inches and 1.129 inches

**Thread Size:**

0.190 inches rod connection

**Material:**

Steel comp 321

**Material Specification:**

Ams 5645 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A264a0

**Mil-std (military Standard):**

Mil-s-5002 spec.