

View Online at <https://aerobasegroup.com/nsn/5340-01-019-7376>

**Fabrication Method (non-core):**

Extruded

**First Leg Length:**

0.500 inches

**Second Leg Length:**

0.810 inches

**Second Leg Width:**

Between 1.248 inches and 1.252 inches

**First Leg Hole Diameter:**

Between 0.128 inches and 0.131 inches

**Second Leg Hole Diameter:**

Between 0.470 inches and 0.480 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.620 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.340 inches

**First Leg Thickness:**

0.062 inches

**Second Leg Thickness:**

0.062 inches

**First Leg Width:**

Between 1.248 inches and 1.252 inches

**First Leg Distance Between Hole Centers Along Width:**

0.937 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.150 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-200/3, t4 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.