

View Online at <https://aerobasegroup.com/nsn/5340-01-019-7376>

Fabrication Method (non-core):

Extruded

First Leg Length:

0.500 inches

Second Leg Length:

0.810 inches

Second Leg Width:

Between 1.248 inches and 1.252 inches

First Leg Hole Diameter:

Between 0.128 inches and 0.131 inches

Second Leg Hole Diameter:

Between 0.470 inches and 0.480 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.620 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.340 inches

First Leg Thickness:

0.062 inches

Second Leg Thickness:

0.062 inches

First Leg Width:

Between 1.248 inches and 1.252 inches

First Leg Distance Between Hole Centers Along Width:

0.937 inches

First Leg Distance From Edge To Hole Center Along Width:

0.150 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-200/3, t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.