

View Online at <https://aerobasegroup.com/nsn/5340-01-023-7136>

**Mounting Hole Type:**

Counterbored

**First Leg Length:**

2.250 inches

**Second Leg Length:**

2.940 inches

**Second Leg Width:**

3.500 inches

**First Leg Hole Diameter:**

Between 0.500 inches and 0.530 inches

**Second Leg Hole Diameter:**

Between 0.410 inches and 0.440 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.375 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.375 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.060 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.565 inches

**First Leg Thickness:**

0.380 inches

**Second Leg Thickness:**

0.380 inches

**First Leg Width:**

3.500 inches

**First Leg End Width:**

2.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.752 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Style:**

Square and tapered

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

105.0 degrees

**Material:**

Steel

**Material Specification:**

Qq-s-741 federal specification single material response

**Surface Treatment:**

Phosphate and enamel

**Surface Treatment Specification:**

Mil-p-16232, type2, class1 military specification single treatment response and tt-e-529 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-p-16232 spec.