

View Online at <https://aerobasegroup.com/nsn/5340-01-023-7136>

Mounting Hole Type:

Counterbored

First Leg Length:

2.250 inches

Second Leg Length:

2.940 inches

Second Leg Width:

3.500 inches

First Leg Hole Diameter:

Between 0.500 inches and 0.530 inches

Second Leg Hole Diameter:

Between 0.410 inches and 0.440 inches

Second Leg Distance Between Hole Centers Along Width:

1.375 inches

Second Leg Distance Between Hole Centers Along Length:

1.375 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.060 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.565 inches

First Leg Thickness:

0.380 inches

Second Leg Thickness:

0.380 inches

First Leg Width:

3.500 inches

First Leg End Width:

2.500 inches

First Leg Distance From Edge To Hole Center Along Width:

1.752 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

105.0 degrees

Material:

Steel

Material Specification:

Qq-s-741 federal specification single material response

Surface Treatment:

Phosphate and enamel

Surface Treatment Specification:

Mil-p-16232, type2, class1 military specification single treatment response and tt-e-529 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-p-16232 spec.