Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-027-3173

| First Leg Length: |
|--|
| 0.960 inches |
| Second Leg Length: |
| 1.560 inches |
| Second Leg Width: |
| 0.540 inches |
| First Leg Slot Length: |
| 0.500 inches |
| First Leg Slot Width: |
| 0.187 inches |
| Second Leg Hole Diameter: |
| 0.187 inches |
| Second Leg Distance From Edge To Hole Center Along Width: |
| 0.270 inches |
| Second Leg Distance From Edge To Hole Center Along Length: |
| 1.250 inches |
| First Leg Thickness: |
| 0.090 inches |
| Second Leg Thickness: |
| 0.090 inches |
| First Leg Width: |
| 0.540 inches |
| First Leg Distance From Edge To Hole Center Along Width: |
| 0.270 inches |
| First Leg Distance From Edge To Hole Center Along Length: |
| 0.460 inches |
| First Leg Style: |
| Square |
| First Leg Hole Arrangement Style: |
| One slot |
| Second Leg Style: |
| Square |
| Second Leg Hole Arrangement Style: |
| One hole |
| Second Leg Relationship To First Leg: |
| Not identical |
| First Leg Angle: |
| |
| 90.0 degrees |
| 90.0 degrees Material: |
| · |

Qq-a-250/11, t4 federal specification single material response

NSN 5340-01-027-3173

Angle Bracket - Page 2 of 2



Surface Treatment:

Oxide film

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.