NSN 5340-01-029-9114

Swivel Caster - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-029-9114

| Center To Center Distance Between Bolt Holes Along Width: |
|--|
| 1.750 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 2.875 inches |
| Wheel Quantity: |
| 1 |
| Safe Operating Load Rating: |
| 400.0 pounds |
| Material And Location: |
| Steel plate err-100 err-100 |
| Surface Treatment And Location: |
| Lacquer, blue plate |
| Wheel Type: |
| Built up |
| Wheel Diameter: |
| 3.500 inches |
| Effective Height: |
| 4.750 inches |
| Features Provided: |
| Axle lubrication fitting and swivel lubrication fitting |
| Plate Style: |
| Rectangular |
| Wheel Bearing Type: |
| Ball |
| Swivel Bearing Type: |
| Ball |
| Swivel Bearing Arrangement: |
| Two row |
| Tread Width: |
| 1.250 inches |
| Caster Plate Length: |
| 3.625 inches |
| Caster Plate Width: |
| 2.500 inches |
| Caster Plate Mounting Hole Diameter: |
| 0.250 inches |
| Style Designator: |
| Swivel offset |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 5340-01-029-9114

Swivel Caster - Page 2 of 2



Demilitarization:

No

Fiig:

A25600