## NSN 5340-01-030-3513

Loop Clamp - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-030-3513

Round, unthreaded  Cushioning Environmental Protection: Heat  Overall Width: 0.500 inches  Diameter:  Between 0.199 inches and 0.209 inches  Material Thickness: Between 0.0285 inches and 0.0355 inches  Center To Center Distance Between Loop And Mounting Hole: Between 0.968 inches and 0.998 inches  Distance From Loop Center To Tongue End: 1.201 inches  Loop Inside Diameter: Between 1.048 inches and 1.078 inches  Material: Steel comp 302 band or steel comp 321 band  Material Specification:	Tongue Hole Type:
Cushioning Environmental Protection: Heat Overall Width: 0.500 inches Diameter: Between 0.199 inches and 0.209 inches Material Thickness: Between 0.0285 inches and 0.0355 inches Center To Center Distance Between Loop And Mounting Hole: Between 0.968 inches and 0.998 inches Distance From Loop Center To Tongue End: 1.201 inches Loop Inside Diameter: Between 1.048 inches and 1.078 inches Material: Steel comp 302 band or steel comp 321 band Material Specification: Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A12700 Mil-std (military Standard):	
Heat Overall Width: 0.500 inches Diameter: Between 0.199 inches and 0.209 inches Material Thickness: Between 0.0285 inches and 0.0355 inches Center To Center Distance Between Loop And Mounting Hole: Between 0.968 inches and 0.998 inches Distance From Loop Center To Tongue End: 1.201 inches Loop Inside Diameter: Between 1.048 inches and 1.078 inches Material: Steel comp 302 band or steel comp 321 band Material Specification: Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A12700 Mil-std (military Standard):	
Overall Width:  0.500 inches  Diameter:  Between 0.199 inches and 0.209 inches  Material Thickness:  Between 0.0285 inches and 0.0355 inches  Center To Center Distance Between Loop And Mounting Hole:  Between 0.968 inches and 0.998 inches  Distance From Loop Center To Tongue End:  1.201 inches  Loop Inside Diameter:  Between 1.048 inches and 1.078 inches  Material:  Steel comp 302 band or steel comp 321 band  Material Specification:  Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A12700  Mil-std (military Standard):	-
Diameter:  Between 0.199 inches and 0.209 inches  Material Thickness:  Between 0.0285 inches and 0.0355 inches  Center To Center Distance Between Loop And Mounting Hole:  Between 0.988 inches and 0.998 inches  Distance From Loop Center To Tongue End: 1.201 inches  Loop Inside Diameter:  Between 1.048 inches and 1.078 inches  Material:  Steel comp 302 band or steel comp 321 band  Material Specification:  Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A12700  Mil-std (military Standard):	
Diameter:  Between 0.199 inches and 0.209 inches  Material Thickness:  Between 0.0285 inches and 0.0355 inches  Center To Center Distance Between Loop And Mounting Hole:  Between 0.968 inches and 0.998 inches  Distance From Loop Center To Tongue End:  1.201 inches  Loop Inside Diameter:  Between 1.048 inches and 1.078 inches  Material:  Steel comp 302 band or steel comp 321 band  Material Specification:  Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A12700  Mil-std (military Standard):	
Between 0.199 inches and 0.209 inches  Material Thickness:  Between 0.0285 inches and 0.0355 inches  Center To Center Distance Between Loop And Mounting Hole:  Between 0.968 inches and 0.998 inches  Distance From Loop Center To Tongue End:  1.201 inches  Loop Inside Diameter:  Between 1.048 inches and 1.078 inches  Material:  Steel comp 302 band or steel comp 321 band  Material Specification:  Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A12700  Mil-std (military Standard):	
Material Thickness: Between 0.0285 inches and 0.0355 inches Center To Center Distance Between Loop And Mounting Hole: Between 0.968 inches and 0.998 inches Distance From Loop Center To Tongue End: 1.201 inches Loop Inside Diameter: Between 1.048 inches and 1.078 inches Material: Steel comp 302 band or steel comp 321 band Material Specification: Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: A12700 Mil-std (military Standard):	
Between 0.0285 inches and 0.0355 inches  Center To Center Distance Between Loop And Mounting Hole:  Between 0.968 inches and 0.998 inches  Distance From Loop Center To Tongue End:  1.201 inches  Loop Inside Diameter:  Between 1.048 inches and 1.078 inches  Material:  Steel comp 302 band or steel comp 321 band  Material Specification:  Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A12700  Mil-std (military Standard):	
Center To Center Distance Between Loop And Mounting Hole:  Between 0.968 inches and 0.998 inches  Distance From Loop Center To Tongue End:  1.201 inches  Loop Inside Diameter:  Between 1.048 inches and 1.078 inches  Material:  Steel comp 302 band or steel comp 321 band  Material Specification:  Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A12700  Mil-std (military Standard):	Material Thickness:
Between 0.968 inches and 0.998 inches  Distance From Loop Center To Tongue End:  1.201 inches  Loop Inside Diameter:  Between 1.048 inches and 1.078 inches  Material:  Steel comp 302 band or steel comp 321 band  Material Specification:  Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A12700  Mil-std (military Standard):	Between 0.0285 inches and 0.0355 inches
Distance From Loop Center To Tongue End:  1.201 inches  Loop Inside Diameter:  Between 1.048 inches and 1.078 inches  Material:  Steel comp 302 band or steel comp 321 band  Material Specification:  Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig: A12700  Mil-std (military Standard):	Center To Center Distance Between Loop And Mounting Hole:
1.201 inches  Loop Inside Diameter:  Between 1.048 inches and 1.078 inches  Material:  Steel comp 302 band or steel comp 321 band  Material Specification:  Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A12700  Mil-std (military Standard):	Between 0.968 inches and 0.998 inches
Loop Inside Diameter:  Between 1.048 inches and 1.078 inches  Material:  Steel comp 302 band or steel comp 321 band  Material Specification:  Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:  A12700  Mil-std (military Standard):	Distance From Loop Center To Tongue End:
Between 1.048 inches and 1.078 inches  Material: Steel comp 302 band or steel comp 321 band  Material Specification: Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A12700 Mil-std (military Standard):	1.201 inches
Material: Steel comp 302 band or steel comp 321 band Material Specification: Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A12700 Mil-std (military Standard):	Loop Inside Diameter:
Steel comp 302 band or steel comp 321 band  Material Specification:  Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A12700  Mil-std (military Standard):	Between 1.048 inches and 1.078 inches
Material Specification:  Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life:  N/a Unit Of Measure: Demilitarization: No Fiig: A12700 Mil-std (military Standard):	Material:
Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band Shelf Life:  N/a Unit Of Measure: Demilitarization: No Fiig: A12700 Mil-std (military Standard):	Steel comp 302 band or steel comp 321 band
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A12700 Mil-std (military Standard):	Material Specification:
N/a Unit Of Measure: Demilitarization: No Fiig: A12700 Mil-std (military Standard):	Mil-s-5059 military specification 1st material response band or ams 5510 assn standard 2nd material response band
Unit Of Measure: Demilitarization: No Fiig: A12700 Mil-std (military Standard):	Shelf Life:
Demilitarization:  No Fiig: A12700 Mil-std (military Standard):	N/a
No Fiig: A12700 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A12700 Mil-std (military Standard):	
Fiig: A12700 Mil-std (military Standard):	Demilitarization:
A12700 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A12700
Mil-s-5059 spec.	Mil-std (military Standard):
	Mil-s-5059 spec.