

View Online at <https://aerobasegroup.com/nsn/5340-01-033-9012>

Fabrication Method (non-core):

Machined

First Leg Length:

0.880 inches

Second Leg Length:

1.500 inches

Second Leg End Width:

0.800 inches

First Leg Hole Diameter:

0.155 inches

Second Leg Hole Diameter:

0.130 inches

Second Leg Distance Between Lower Hole Centers Along Width:

0.466 inches

Second Leg Distance Between Hole Centers Along Length:

0.466 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.380 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.400 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.550 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

1.250 inches

First Leg Distance Between Hole Centers Along Width:

0.550 inches

First Leg Distance From Edge To Hole Center Along Width:

0.380 inches

First Leg Distance From Edge To Hole Center Along Length:

0.400 inches

First Leg End Radius:

0.630 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

120.0 degrees

Second Leg Offset Angle:

55.0 degrees

Material:

Aluminum

Material Specification:

Ls2229 fscm 98897 mfr ref single material response

Surface Treatment:

Passivate

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0