

View Online at <https://aerobasegroup.com/nsn/5340-01-033-9012>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

0.880 inches

**Second Leg Length:**

1.500 inches

**Second Leg End Width:**

0.800 inches

**First Leg Hole Diameter:**

0.155 inches

**Second Leg Hole Diameter:**

0.130 inches

**Second Leg Distance Between Lower Hole Centers Along Width:**

0.466 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.466 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

0.380 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.400 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.550 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

1.250 inches

**First Leg Distance Between Hole Centers Along Width:**

0.550 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.380 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.400 inches

**First Leg End Radius:**

0.630 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Angle

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

120.0 degrees

**Second Leg Offset Angle:**

55.0 degrees

**Material:**

Aluminum

**Material Specification:**

Ls2229 fscm 98897 mfr ref single material response

**Surface Treatment:**

Passivate

**Style Designator:**

Offset angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0