

View Online at <https://aerobasegroup.com/nsn/5340-01-035-2312>

Fabrication Method (non-core):

Stamped

Mounting Hole Type:

Threaded

First Leg Length:

0.620 inches

Second Leg Length:

1.880 inches

Second Leg Width:

2.250 inches

Second Leg End Width:

1.750 inches

First Leg Hole Diameter:

0.164 inches

Second Leg Hole Diameter:

0.112 inches

Second Leg Distance Between Hole Centers Along Width:

1.750 inches

Second Leg Distance Between Hole Centers Along Length:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.790 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

2.250 inches

First Leg Distance Between Hole Centers Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.380 inches

First Leg Distance From Edge To Hole Center Along Length:

0.240 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 1020

Material Specification:

Qq-s-698 federal specification single material response

Surface Treatment:

Cadmium and chromate

Special Test Features (non-core):

Special quality control testing

Surface Treatment Specification:

Qq-p-416, type 2, cl 1 federal specification single treatment response

Style Designator:

Angle

Reference Number Differentiating Characteristics:

As differentiated by packaging in accordance with mil-p-23199 and material conforming to ships parts control center special quality control provisioning

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0