

View Online at <https://aerobasegroup.com/nsn/5340-01-035-2312>

**Fabrication Method (non-core):**

Stamped

**Mounting Hole Type:**

Threaded

**First Leg Length:**

0.620 inches

**Second Leg Length:**

1.880 inches

**Second Leg Width:**

2.250 inches

**Second Leg End Width:**

1.750 inches

**First Leg Hole Diameter:**

0.164 inches

**Second Leg Hole Diameter:**

0.112 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.750 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.310 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.790 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

2.250 inches

**First Leg Distance Between Hole Centers Along Width:**

1.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.380 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.240 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square and tapered

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1020

**Material Specification:**

Qq-s-698 federal specification single material response

**Surface Treatment:**

Cadmium and chromate

**Special Test Features (non-core):**

Special quality control testing

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 1 federal specification single treatment response

**Style Designator:**

Angle

**Reference Number Differentiating Characteristics:**

As differentiated by packaging in accordance with mil-p-23199 and material conforming to ships parts control center special quality control provisioning

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0