NSN 5340-01-035-8249

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-035-8249

Fabrication Method (non-core):

Formed

Second Leg Length:

Between 2.471 inches and 2.511 inches

Second Leg Width:

Between 0.545 inches and 0.575 inches

First Leg Hole Diameter:

Between 0.216 inches and 0.226 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance Between Hole Centers Along Length:

1.604 mils and 1.624 centimeters

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.270 inches and 0.290 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.270 inches and 0.290 inches

First Leg Thickness:

Between 0.056 inches and 0.062 inches

Second Leg Thickness:

Between 0.056 inches and 0.062 inches

Center Section Width:

Between 0.545 inches and 0.575 inches

Center Section Thickness:

Between 0.056 inches and 0.062 inches

First Leg Width:

Between 0.545 inches and 0.575 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.270 inches and 0.290 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg End Radius:

Between 0.469 inches and 0.531 inches

Second Leg End Radius:

Between 0.469 inches and 0.531 inches

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

NSN 5340-01-035-8249

Double Angle Bracket - Page 2 of 2



| First Leg Angle: |
|---|
| 15.0 degrees |
| Second Leg Angle: |
| 90.0 degrees |
| Material: |
| Steel comp 410 |
| Material Specification: |
| Ams 5504 assn standard single material response |
| Style Designator: |
| Double angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A042a0