## NSN 5340-01-036-2160

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-036-2160

Fabrication Method (non-core):
Stamped
First Leg Length:
0.500 inches
Second Leg Length:
1.500 inches
Second Leg Width:
0.875 inches
First Leg Hole Diameter:
0.128 inches
Second Leg Hole Diameter:
0.157 inches
Second Leg Distance Between Hole Centers Along Length:
0.750 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.422 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.250 inches
First Leg Thickness:
0.062 inches
Second Leg Thickness:
0.062 inches
First Leg Width:
0.875 inches
First Leg Distance Between Hole Centers Along Width:
0.625 inches
First Leg Distance From Edge To Hole Center Along Width:
0.125 inches
First Leg Distance From Edge To Hole Center Along Length:
0.250 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:

90.0 degrees

## NSN 5340-01-036-2160

Angle Bracket - Page 2 of 2

No Fiig: A042a0



Special Features:
A 3rd hole 0.209 in. Dia. 0.625 in. From end 0.281 in. Between center lines of second end
Heat Treatment:
T-6 solution heat treated
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-250/11, t6 federal specification single material response
Surface Treatment:
Iridium
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: