

View Online at <https://aerobasegroup.com/nsn/5340-01-036-2160>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.500 inches

Second Leg Length:

1.500 inches

Second Leg Width:

0.875 inches

First Leg Hole Diameter:

0.128 inches

Second Leg Hole Diameter:

0.157 inches

Second Leg Distance Between Hole Centers Along Length:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.422 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.062 inches

Second Leg Thickness:

0.062 inches

First Leg Width:

0.875 inches

First Leg Distance Between Hole Centers Along Width:

0.625 inches

First Leg Distance From Edge To Hole Center Along Width:

0.125 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

A 3rd hole 0.209 in. Dia. 0.625 in. From end 0.281 in. Between center lines of second end

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Iridium

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0