

View Online at <https://aerobasegroup.com/nsn/5340-01-037-2707>

**Fabrication Method (non-core):**

Forged

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.940 inches

**Second Leg Length:**

3.750 inches

**Second Leg Width:**

7.500 inches

**First Leg Hole Diameter:**

Between 1.3128 inches and 1.3138 inches

**Second Leg Hole Diameter:**

Between 0.498 inches and 0.508 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.625 inches

**Second Leg Distance Between Hole Centers Along Length:**

2.000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.625 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.875 inches

**First Leg Thickness:**

0.440 inches

**Second Leg Thickness:**

0.440 inches

**First Leg Width:**

7.500 inches

**First Leg End Width:**

1.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

3.750 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**First Leg Style:**

Square and tapered

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Four additional 0.500 in. Diameter holes second leg

**Material:**

Steel comp 4340

**Material Specification:**

Mil-s-16974 military specification single material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Mil-p-16233, type m, class 4 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-s-16974 spec.