NSN 5340-01-038-0571

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-038-0571

Fabrication Method (non-core):
Welded
First Leg Length:
3.250 inches
Second Leg Length:
9.350 inches
Reinforcement Method (non-core):
Gusset center section
Second Leg Width:
3.250 inches
First Leg Hole Diameter:
Between 0.312 inches and 0.326 inches
Second Leg Hole Diameter:
Between 0.312 inches and 0.336 inches
Second Leg Distance Between Hole Centers Along Width:
2.250 inches
Second Leg Distance Between Hole Centers Along Length:
6.560 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.500 inches
First Leg Thickness:
0.190 inches
Second Leg Thickness:
0.190 inches
First Leg Width:
3.250 inches
First Leg Distance Between Hole Centers Along Width:
2.500 inches
First Leg Distance Between Hole Centers Along Length:
2.000 inches
First Leg Distance From Edge To Hole Center Along Width:
0.350 inches
First Leg Distance From Edge To Hole Center Along Length:
0.410 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Four holes
Second Leg Style:

Square

NSN 5340-01-038-0571 Angle Bracket - Page 2 of 2



econd Leg Hole Arrangement Style:
our holes
econd Leg Relationship To First Leg:
lot identical
irst Leg Angle:
0.0 degrees
laterial:
luminum alloy 5086 and aluminum alloy 5083
laterial Specification:
2q-s-250/7, h32 federal specification 1st material response and qq-a-250/6, h321 federal specification 2nd material response
tyle Designator:
ingle
helf Life:
l/a
Init Of Measure:
Demilitarization:
lo
iig:
.042a0