

View Online at <https://aerobasegroup.com/nsn/5340-01-040-5940>

**First Leg Length:**

0.750 inches

**Second Leg Length:**

1.750 inches

**End Application:**

Tf33-pw-100/100a engine

**Second Leg Width:**

1.110 inches

**Second Leg Corner Radius:**

0.320 inches

**Second Leg End Width:**

1.400 inches

**First Leg Hole Diameter:**

Between 0.218 inches and 0.229 inches

**Second Leg Hole Diameter:**

Between 0.342 inches and 0.354 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.780 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.040 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.300 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.300 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

1.110 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.440 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.320 inches

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

162.0 degrees

**Second Leg Offset Angle:**

37.0 degrees

**Special Features:**

2nd leg, 2 holes as stated above, 2 holes 0.218-0.229 in. Dia

**Material:**

Steel comp 321

**Material Specification:**

Mil-s-6721 military specification single material response

**Style Designator:**

Offset angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-s-6721 spec.