

View Online at <https://aerobasegroup.com/nsn/5340-01-044-2047>

**First Leg Length:**

26.900 millimeters

**Second Leg Length:**

96.800 millimeters

**Reinforcement Method (non-core):**

Rib stiffener both ends

**Second Leg Width:**

32.000 millimeters

**First Leg Hole Diameter:**

Between 8.600 millimeters and 9.100 millimeters

**Second Leg Hole Diameter:**

Between 23.000 millimeters and 23.500 millimeters

**Second Leg Distance From Edge To Hole Center Along Width:**

16.000 millimeters

**Second Leg Distance From Edge To Hole Center Along Length:**

17.000 millimeters

**First Leg Thickness:**

Between 2.000 millimeters and 2.350 millimeters

**Second Leg Thickness:**

Between 2.000 millimeters and 2.350 millimeters

**First Leg Width:**

32.000 millimeters

**First Leg Distance From Edge To Hole Center Along Width:**

16.000 millimeters

**First Leg Distance From Edge To Hole Center Along Length:**

10.400 millimeters

**Second Leg End Radius:**

17.000 millimeters

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1010

**Surface Treatment:**

Zinc

**Surface Treatment Specification:**

P-44-a-16764 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0