
NSN 5340-01-046-2630

Angle Bracket - Page 1 of 2





First Leg Length:	
1.500 inches	
Second Leg Length:	
2.120 inches	
Second Leg Width:	
1.800 inches	
Second Leg Corner Radius:	
0.620 inches	
First Leg Hole Diameter:	
Between 0.343 inches and 0.350 inches	
Second Leg Slot Length:	
1.250 inches	
Second Leg Slot Width:	
0.380 inches	
First Leg Thickness:	
0.188 inches	
Second Leg Thickness:	
0.188 inches	
First Leg Width:	
3.500 inches	
First Leg Corner Radius:	
0.380 inches	
First Leg Distance From Edge To Hole Center Along Width:	
0.620 inches	
First Leg Distance From Edge To Hole Center Along Length:	
0.500 inches	
First Leg Distance Between First And Second Hole Centers Along Length:	
1.250 inches	
First Leg Distance Between Second And Third Hole Centers Along Length:	
1.250 inches	
First Leg Style:	
Corner radius	
First Leg Hole Arrangement Style:	
Three holes	
Second Leg Style:	
Corner radius	
Second Leg Hole Arrangement Style:	
One slot	
Second Leg Relationship To First Leg:	
Not identical	
First Leg Angle:	
90.0 degrees	

NSN 5340-01-046-2630

Angle Bracket - Page 2 of 2



Material:

Steel comp 634 or steel comp 4130

Material Specification:

Qq-s-634, c1080 federal specification 1st material response or aisi/sae 4130 assn standard 2nd material response

Surface Treatment:

Zinc

Surface Treatment Specification:

Qq-z-325, type 2, class 1 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0