

View Online at <https://aerobasegroup.com/nsn/5340-01-047-8002>

Mounting Hole Type:

Countersunk

First Leg Length:

0.625 inches

Second Leg Length:

0.688 inches

Second Leg Width:

1.000 inches

First Leg Hole Diameter:

Between 0.097 inches and 0.102 inches

Second Leg Hole Diameter:

Between 0.127 inches and 0.133 inches

Second Leg Distance Between Hole Centers Along Width:

0.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.187 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.188 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

1.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.344 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

0.344 inches

First Leg Distance From Edge To Hole Center Along Width:

0.156 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg End Radius:

0.188 inches

Second Leg End Radius:

0.500 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Countersunk hole first leg 0.170 in. Dia

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/4, temper o federal specification single material response

Surface Treatment:

Anodize and primer

Style Designator:

Angle

Specification Data:

26512-gb11d9-1 manufacturers specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0