
# NSN 5340-01-048-1281

Rigid Caster - Page 1 of 2



# **End Application:**

W/s: support equipment, f-4 aircraft

# Wheel Quantity:

1

# Safe Operating Load Rating:

250.0 pounds

# Material And Location:

Steel wheel rim err-100 err-100

#### Wheel Type:

Semipneumatic tire

## Wheel Diameter:

6.000 inches

# Effective Height:

7.375 inches

#### **Features Provided:**

Spacer and washer

# Plate Style:

Square

# Wheel Bearing Type:

Plain, self-lubricated

#### **Tread Width:**

2.000 inches

#### Caster Plate Length:

6.250 inches

## Caster Plate Width:

4.500 inches

## Center To Center Major Distance Between Mounting Slots Along Length:

5.250 inches

#### Center To Center Minor Distance Between Mounting Slots Along Length:

4.938 inches

#### Center To Center Major Distance Between Mounting Slots Along Width:

3.375 inches

#### Center To Center Minor Distance Between Mounting Slots Along Width:

2.438 inches

#### Caster Plate Mounting Slot Length:

Any acceptable

## **Caster Plate Mounting Slot Width:**

0.391 inches

#### Style Designator:

Rigid

## Shelf Life:

N/a



# NSN 5340-01-048-1281

Rigid Caster - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A25600

