NSN 5340-01-048-6851

Butt Hinge - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-048-6851

Overall Length:
13.250 inches
Material Thickness:
0.060 inches
Mounting Hole Diameter:
Between 0.191 inches and 0.196 inches
Mounting Hole Quantity:
18
Pin Diameter:
Between 0.185 inches and 0.189 inches
Performance Type:
Not rated
Reversible Feature:
Included
Hinge Mounting Type:
Full surface
Pin Removability:
Removable
Rising Pin:
Not included
Knuckle Quantity:
Knuckle Quantity:
•
6
6 Pin Center To Body Edge Distance:
6 Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches
Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches Knuckle Type:
Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches Knuckle Type: Friction
Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches Knuckle Type: Friction Material And Location:
Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches Knuckle Type: Friction Material And Location: Steel, qq-s-698 body err-100 err-100
Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches Knuckle Type: Friction Material And Location: Steel, qq-s-698 body err-100 err-100 Surface Treatment And Location:
Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches Knuckle Type: Friction Material And Location: Steel, qq-s-698 body err-100 err-100 Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 1
Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches Knuckle Type: Friction Material And Location: Steel, qq-s-698 body err-100 err-100 Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 1 Style Designator:
Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches Knuckle Type: Friction Material And Location: Steel, qq-s-698 body err-100 err-100 Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 1 Style Designator: Butt
Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches Knuckle Type: Friction Material And Location: Steel, qq-s-698 body err-100 err-100 Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 1 Style Designator: Butt Shelf Life:
Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches Knuckle Type: Friction Material And Location: Steel, qq-s-698 body err-100 err-100 Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 1 Style Designator: Butt Shelf Life: N/a
Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches Knuckle Type: Friction Material And Location: Steel, qq-s-698 body err-100 err-100 Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 1 Style Designator: Butt Shelf Life: N/a
Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches Knuckle Type: Friction Material And Location: Steel, qq-s-698 body err-100 err-100 Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 1 Style Designator: Butt Shelf Life: N/a Unit Of Measure:
Pin Center To Body Edge Distance: Between 0.969 inches and 1.031 inches Knuckle Type: Friction Material And Location: Steel, qq-s-698 body err-100 err-100 Surface Treatment And Location: Cadmium, qq-p-416, type 2, class 1 Style Designator: Butt Shelf Life: N/a Unit Of Measure: Demilitarization: