

View Online at <https://aerobasegroup.com/nsn/5340-01-051-5554>

Fabrication Method (non-core):

Stamped

First Leg Length:

1.000 inches

Second Leg Length:

1.000 inches

Reinforcement Method (non-core):

Turned edge both ends

Second Leg Width:

0.750 inches

First Leg Hole Diameter:

0.086 inches

Second Leg Hole Diameter:

Between 0.297 inches and 0.328 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.375 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.438 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

0.750 inches

First Leg Distance Between Hole Centers Along Length:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Length:

0.125 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/8, t6 federal specification single material response

Surface Treatment:

Anodize

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0