

View Online at <https://aerobasegroup.com/nsn/5340-01-054-6653>

First Leg Length:

0.500 inches

Second Leg Length:

0.500 inches

Second Leg Width:

Between 2.100 inches and 2.140 inches

First Leg Hole Diameter:

Between 0.142 inches and 0.152 inches

Second Leg Hole Diameter:

Between 0.142 inches and 0.152 inches

Second Leg Distance Between Hole Centers Along Width:

Between 1.640 inches and 1.660 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.225 inches and 0.245 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.178 inches and 0.198 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 2.100 inches and 2.140 inches

First Leg Distance Between Lower Hole Centers Along Width:

Between 1.364 inches and 1.384 inches

First Leg Distance Between Hole Centers Along Length:

Between 0.083 inches and 0.103 inches

First Leg Distance Between First And Second Hole Centers Along Width:

Between 0.677 inches and 0.697 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.375 inches and 0.379 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.116 inches and 0.136 inches

First Leg Style:

Extended flat

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Extended flat

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6063

Material Specification:

Qq-a-200/9, t5 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, class 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.