

View Online at <https://aerobasegroup.com/nsn/5340-01-054-6653>

**First Leg Length:**

0.500 inches

**Second Leg Length:**

0.500 inches

**Second Leg Width:**

Between 2.100 inches and 2.140 inches

**First Leg Hole Diameter:**

Between 0.142 inches and 0.152 inches

**Second Leg Hole Diameter:**

Between 0.142 inches and 0.152 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 1.640 inches and 1.660 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.225 inches and 0.245 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.178 inches and 0.198 inches

**First Leg Thickness:**

Between 0.056 inches and 0.068 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.068 inches

**First Leg Width:**

Between 2.100 inches and 2.140 inches

**First Leg Distance Between Lower Hole Centers Along Width:**

Between 1.364 inches and 1.384 inches

**First Leg Distance Between Hole Centers Along Length:**

Between 0.083 inches and 0.103 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

Between 0.677 inches and 0.697 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.375 inches and 0.379 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.116 inches and 0.136 inches

**First Leg Style:**

Extended flat

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Extended flat

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6063

**Material Specification:**

Qq-a-200/9, t5 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, class 3 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.