

View Online at <https://aerobasegroup.com/nsn/5340-01-056-1569>

Mounting Hole Type:

Countersunk

First Leg Length:

0.800 inches

Second Leg Length:

0.810 inches

Second Leg Width:

0.302 inches

First Leg Hole Diameter:

Between 0.195 inches and 0.201 inches

Second Leg Hole Diameter:

Between 0.085 inches and 0.094 inches

Second Leg Distance Between Hole Centers Along Length:

1.847 mils and 1.857 centimeters

Second Leg Distance From Edge To Hole Center Along Width:

0.225 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.169 inches

First Leg Thickness:

0.188 inches

Second Leg Thickness:

0.188 inches

First Leg Width:

2.210 inches

First Leg Distance Between Hole Centers Along Length:

1.710 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second leg is c shaped with top portion of c 0.282 in. Leg width, bottom portion of c 0.302 in. Leg width with 1.626 in. Space between top and bottom

Material:

Aluminum alloy 5086

Material Specification:

Qq-a-200/5, h111 federal specification single material response

Surface Treatment:

Oxide film

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.