

View Online at <https://aerobasegroup.com/nsn/5340-01-056-7654>

Mounting Hole Type:

Counterbored

First Leg Length:

1.125 inches

Second Leg Length:

1.188 inches

Second Leg Width:

2.500 inches

Second Leg Corner Radius:

0.125 inches

First Leg Hole Diameter:

Between 0.217 inches and 0.219 inches

Second Leg Hole Diameter:

Between 0.145 inches and 0.152 inches

Second Leg Distance Between Hole Centers Along Width:

0.750 inches

Second Leg Distance Between Hole Centers Along Length:

0.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.875 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.125 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

2.500 inches

First Leg Distance Between Upper Hole Centers Along Width:

2.000 inches

First Leg Distance Between Hole Centers Along Length:

0.500 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.062 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

2.000 in. Lg slot located on second end

Material:

Aluminum alloy 6061

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-std-171, no. 7.3 military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.