

View Online at <https://aerobasegroup.com/nsn/5340-01-057-9396>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

0.630 inches

**Second Leg Length:**

1.000 inches

**Second Leg Width:**

0.500 inches

**First Leg Hole Diameter:**

Between 0.200 inches and 0.205 inches

**Second Leg Hole Diameter:**

0.098 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.370 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

0.880 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**Second Leg End Radius:**

0.250 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Right hand offset

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5, alclad t3 federal specification single material response

**Surface Treatment:**

Chromate and paint

**Surface Treatment Specification:**

Mil-c-5541 military specification 1st treatment response and nai-1269 fscm 76823 mfr ref 2nd treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.