

View Online at <https://aerobasegroup.com/nsn/5340-01-058-8481>

Fabrication Method (non-core):

Cast

Mounting Hole Type:

Counterbored and threaded

First Leg Length:

1.427 inches

Second Leg Length:

3.625 inches

Second Leg Width:

1.375 inches

Second Leg Corner Radius:

0.063 inches

Err Default:

Err default

First Leg Hole Diameter:

Between 0.156 inches and 0.203 inches

Second Leg Distance Between Hole Centers Along Length:

2.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.6875 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.375 inches

Second Leg Slot Length:

0.500 inches

Second Leg Slot Width:

Between 0.280 inches and 0.290 inches

First Leg Thickness:

0.6875 inches

Second Leg Thickness:

Between 0.234 inches and 0.250 inches

First Leg Diameter:

0.6875 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.739 inches and 0.801 inches

First Leg Distance From Edge To Hole Center Along Length:

0.344 inches

First Leg Style:

Extended rod

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Offset Angle:

15.0 degrees

Special Features:

First leg 1/2-27npt 1/2 deep eachend 6.00 lg rod 90 degrees from second legwhich has 2 holes 0.086-56unc-2b 1.656c-to-c first hole 0.911/0.931 from endc/l 0.6875 from edge and color 27875

Material:

Aluminum alloy 355.0 and aluminum alloy 356.0

Surface Treatment:

Enamel baked

Style Designator:

Offset angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0