

View Online at <https://aerobasegroup.com/nsn/5340-01-059-6742>

Fabrication Method (non-core):

Machined

First Leg Length:

0.700 inches

Second Leg Length:

0.750 inches

Second Leg Width:

1.000 inches

First Leg Hole Diameter:

0.098 inches

Second Leg Hole Diameter:

Between 0.140 inches and 0.145 inches

Second Leg Distance Between Hole Centers Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.900 inches

First Leg Width:

1.000 inches

First Leg Distance Between Hole Centers Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Width:

0.200 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, t 2, cl 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.