

View Online at <https://aerobasegroup.com/nsn/5340-01-062-6504>

Fabrication Method (non-core):

Extruded

Mounting Hole Type:

Countersunk

First Leg Length:

0.350 inches

Second Leg Length:

0.500 inches

Second Leg Width:

6.550 inches

First Leg Hole Diameter:

Between 0.161 inches and 0.164 inches

First Leg Thickness:

0.062 inches

Second Leg Thickness:

0.062 inches

First Leg Width:

6.550 inches

First Leg Distance From Edge To Hole Center Along Width:

0.125 inches

First Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Distance Between First And Second Hole Centers Along Length:

3.075 inches

First Leg Distance Between Second And Third Hole Centers Along Length:

3.075 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6063

Material Specification:

Qq-a-200/9, t6 federal specification single material response

Surface Treatment:

Oxide film

Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.